



GATE SHOWN IS OPTIONAL, STANDARD MODEL IS WITH CHAIN

KeeHatch® *Mightylight* Model KHML-O 3636, this model is attached to the counter flashing KeeHatch in Aluminum

<u>#Q</u>	<u>Kee Lite®</u>	<u>#Q</u>	<u>Pipe</u>	<u>Size</u>	<u>#Q</u>	<u>Item</u>	<u>Size</u>
2	L10-7	4	Stubs	8"	1	"S" hook	
2	L15-7	2	Posts	30"	1	Quick link	
4	121-7	4	Posts	42"	1	Fastclip	
8	133C	4	Rails	48"	16	3/8" X 1 1/4" bolts	
4	L135-77				16	Product Label	
4	L161-7				1	Warranty Card	
2	178-7						

Tools Needed Using RailingReady® Roof Hatches & Mounting to Counter Flashing

- wrench to tighten bolts to Fastclip
- torque wrench
- 5/16" hex key to tighten Kee Klamp® set screws
- bolt cutter to remove excess chain
- drill and bit will be required if hatch is not RailingReady

INSTALLATION

- STEP 1** hold L161-7 against counter flashing, slide fast clip over L161 and behind counter flashing
- STEP 2** bolt L161-7 to Fastclip, repeat for 4 corners
- STEP 3** insert posts into L161-7's, torque set screws to 29 foot pounds
- STEP 4** slide 178-7's onto 30" posts
- STEP 5** insert other rails as per diagram, torque set screws to 29 foot pounds, slide 178-7's to top of 30" posts and torque to 29 foot pounds
- STEP 6** install chain, "S" hook, quick link onto 178-7's. Install 133C plugs

