



GATE SHOWN IS OPTIONAL, STANDARD MODEL IS WITH CHAIN

KeeHatch® Mightylight KHML3054

this model is attached to the counter flashing, KeeHatch in Aluminum

<u>#Q</u>	<u>Kee Lite®</u>	<u>#Q</u>	<u>Pipe</u>	<u>Size</u>	<u>#Q</u>	<u>Item</u>	<u>Size</u>
8	133C plug	4	Posts	42"	1	3/16" Chain	39"
2	121-7	2	Rails	45"	1	"S" hook	
4	L135-77	2	Rails	69"	1	Quick link	
4	L161-7				16	Fastclip	
2	178-7				16	3/8" x 1 1/4" bolts	
					1	Product Label	
					1	Warranty Card	

Tools Needed Using RailingReady® Roof Hatches & Mounting to Counter Flashing

- wrench to tighten bolts to Fastclip
- torque wrench
- 5/16" hex key to tighten Kee Klamp® set screws
- bolt cutter to remove excess chain
- drill and bit will be required if hatch is not RailingReady, hardware is not provided for curb mounting

INSTALLATION

- STEP 1** hold L161-7 against counter flashing, slide fastclip over L161 & behind counter flashing, bolt fast clip
- STEP 2** slide 178-7 onto top rails at exit point and torque to 29 foot pounds
- STEP 3** insert pre-assembled posts into L161-7's, torque set screws to 29 foot pounds
- STEP 4** insert top and mid rails into L135-77 & 121-7, torque set screws to 29 foot pounds, cut off excess pipe
- STEP 5** install chain, "S" hook, quick link & L84-7 plugs